

Rimage 2000i Specifications

This document provides product specification information for the Rimage 2000i autoloader. For more information on how to operate and identify the parts of the Rimage 2000i, refer to the *Rimage 2000i User Guide*.

 **Notes:**

- The most up-to-date 2000i specification information is found in the current revision of this document.
- For 480i printer specifications, refer to the Rimage 480i Specifications document available at www.rimage.com/support. From the **Support** menu select: **Printer Series > Rimage 480i > User Manuals** tab.

	Rimage 2000i								
Standard system	The standard system includes the Rimage 2000i autoloader (with the embedded Rimage 480i printer assembly) and Rimage 2000i Software.								
Number of recorders	2								
Bin capacity	<table> <tr> <td style="padding-left: 20px;">Supply bin</td> <td>100 discs</td> </tr> <tr> <td style="padding-left: 20px;">Output bin</td> <td>100 discs</td> </tr> </table>	Supply bin	100 discs	Output bin	100 discs				
Supply bin	100 discs								
Output bin	100 discs								
Physical size	<table> <tr> <td style="padding-left: 20px;">Height</td> <td>21.0 in (53.3 cm)</td> </tr> <tr> <td style="padding-left: 20px;">Width</td> <td>15.75 in (40.0 cm)</td> </tr> <tr> <td style="padding-left: 20px;">Depth*</td> <td>20.0 in (50.8 cm)</td> </tr> <tr> <td style="padding-left: 20px;">Weight</td> <td>62.0 lb (28.12 kg)</td> </tr> </table> <p>*Leave an additional 3.5 in (9 cm) for cabling.</p>	Height	21.0 in (53.3 cm)	Width	15.75 in (40.0 cm)	Depth*	20.0 in (50.8 cm)	Weight	62.0 lb (28.12 kg)
Height	21.0 in (53.3 cm)								
Width	15.75 in (40.0 cm)								
Depth*	20.0 in (50.8 cm)								
Weight	62.0 lb (28.12 kg)								
Software requirements	The Rimage 2000i ships with Rimage 2000i Software™. The Rimage 2000i operates with either Rimage 2000i Software or Rimage OfficeNET™ Software Suite. To purchase OfficeNET Software Suite, contact your Rimage reseller.								
Media requirements	Use only 120 mm optical discs that are coated with an ink-jet printable surface. The media in Rimage Media Kits™ are designed for optimum print performance.								

Rimage 2000i	
Minimum PC requirements	<p>ⓘ Important! If you do not understand these requirements, ask your computer technician for help or refer to your PC documentation.</p> <ul style="list-style-type: none"> • Windows Vista Business SP1 (OfficeNET Software Suite and Rimage 2000i Software versions 8.2 or higher only) * • Windows XP Professional SP2 (Rimage 2000i Software versions 8.1 and lower only) • Windows XP Professional SP3 • Windows 2000 Professional SP4 (Rimage 2000i Software versions 8.1 and lower only) • Windows Server 2003 <p>Supported operating systems (32-bit only)</p> <p>Processor Celeron 2.0 GHz</p> <p>RAM/Memory 512 MB</p> <p>Fixed storage 2 36 GB, 7200 RPM hard drives**</p> <p>Graphics 1024 x 768 screen resolution, 16-bit color</p> <p>Ports One USB 2.0 port</p> <p><small>*Rimage 2000i autoloaders using a FireWire connection are not supported by the Windows Vista operating system. **For increased performance or DVD/dual-layer disc production, an additional hard drive is recommended.</small></p>
Networking ability	Refer to the <i>Rimage Advanced Setup (Networking) Guide</i> for instructions on submitting orders from a networked computer.
Print quality	<p>Technology Thermal inkjet printing</p> <p>Resolution Up to 4800 dpi</p> <p>Droplet size 3 pico-liters</p> <p>Pixel density 5.76 million pixels per square inch</p>
Power	100 – 240 VAC, 2.7 A, 60/50 Hz
Temperature and humidity	<p>Operating temperature 60° to 95° F (16° to 35° C)</p> <p>Humidity 40% to 80% non-condensing</p> <p>Storage temperature 5° to 95° F (-15° to 35° C)</p>