

Rimage AutoEverest™ and AutoPrism™ AutoPrinter Specifications

This document provides product specification information for the Rimage AutoEverest and AutoPrism AutoPrinters. For more information on how to operate and identify the parts of the AutoEverest and AutoPrism, refer to the *Rimage AutoPrinter User Guide*.

Notes:

- The most up-to-date technical specification information for the AutoEverest and AutoPrism is found in the current revision of this document.
- For printer specifications, refer to the Rimage Everest or Prism printer specifications document available at www.rimage.com/support. From the **Support** menu select: **Printer Series > Printer Name > User Manuals**.

	AutoEverest	AutoPrism
Standard system	AutoPrinter autoloader, Everest printer and, CD Designer™ Software Suite	AutoPrinter autoloader, PrismPlus!™ printer, and CD Designer™ Software Suite
Minimum PC requirements	<p>J Important! If you do not understand these requirements, ask your computer technician for help or refer to your PC documentation.</p>	
Windows PC	<p>Processor: 1 GHz or higher RAM/memory: 512 MB or higher Hard drive: 1GB free space Port: One USB 2.0 Display resolution: 1024x768 or higher Supported operating systems:</p> <ul style="list-style-type: none"> • Windows Vista Business with SP1 (CD Designer 8.1 and higher only)* • Windows Vista Business, Enterprise, and Ultimate with SP1 (CD Designer version 8.2 and higher only)* • Windows XP Professional SP3 • Windows XP Professional SP2 (Rimage Software versions 8.1 and lower only) • Windows 2000 Professional SP4 (Rimage Software versions 8.1 and lower only) • Windows Server 2003 SP1 standard 	<p>Processor: 1 GHz or higher RAM/memory: 512 MB or higher Hard drive: 1GB free space Port: One USB 2.0 Display resolution: 1024x768 or higher Supported operating systems:</p> <ul style="list-style-type: none"> • Windows Vista Business, Ultimate, and Enterprise with SP1 (CD Designer version 8.2 and higher only)* • Windows XP Professional SP3 • Windows XP Professional SP2 (Rimage Software versions 8.1 and lower only) • Windows 2000 Professional SP4 (Rimage Software versions 8.1 and lower only) • Windows Server 2003 SP1 standard
Macintosh	<p>Processor: G4 RAM/memory: 512 MB Port: One USB 2.0 Supported operating systems:</p> <ul style="list-style-type: none"> • Everest II: Macintosh OS X v 10.3/10.4 • Everest III & 600: Macintosh OS X v 10.4/410.5 	Not supported
<p>* Standalone Everest II printers and AutoPrinters using Everest II printers are not supported by the Windows Vista operating system.</p>		

	AutoEverest	AutoPrism
Physical size		
Height	22.5 in (57.2 cm)	22.5 in (57.2 cm)
Width	15 in (38.1 cm)	15 in (38.1 cm)
Depth*	23.5 in (59.7 cm)	23.5 in (59.7 cm)
Weight	82 lb (37.2 kg)	57 lb (25.9 kg)
	*Leave an additional 3.5 in (9 cm) for cabling.	
Prints per hour	Up to 60	Up to 240
Power	100 – 240 VAC, 1.5 A, 60/50 Hz	
Input bin capacity	300 discs	
Output capacity	300 discs	
Software requirements	CD Designer or other graphics application	
Media requirements	Refer to your printer user guide for the correct media requirements. Rimage Media Kits™ are designed for optimum recording and print performance.	
Ribbon requirements	Refer to your printer user guide for the correct printer ribbons. Rimage Media Kits™ include the required print ribbons.	
Label design requirements	Refer to your printer user guide for label design requirements.	
Temperature and humidity		
Operating temperature	60° to 80° F (16° to 27° C)	
Humidity	40% to 80% non-condensing	
Storage temperature	5° to 95° F (-15° to 35° C)	